

IS011064758B2

(12) United States Patent Dervish et al.

(10) Patent No.: US 11,064,758 B2

(45) **Date of Patent:**

Jul. 20, 2021

(54) SOLE OR INNER SOLE

(71) Applicant: **IMPACT TECH LABS AG**, Zurich

(CH)

(72) Inventors: Kemal Dervish, Welwyn Garden City

(GB); Haim Geva, London (GB); Jason Lloyd Roberts, St. Margarets (GB); Giles Tongue, West Byfleet (GB); Grant Trewartha, Wiltshire

(GB)

(73) Assignee: **NURVV LIMITED**, Twickenham (GB)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 16/022,096

(22) Filed: Jun. 28, 2018

(65) Prior Publication Data

US 2019/0000177 A1 Jan. 3, 2019

(30) Foreign Application Priority Data

(51) Int. Cl. A43B 3/00 (2006.01) A43B 13/00 (2006.01)

(Continued)

(52) U.S. Cl.

(Continued)

(58) Field of Classification Search

CPC A43B 3/0005; A43B 7/142; A43B 7/1425; A43B 7/1435; A43B 7/144; A43B 7/145; (Continued)

(56) References Cited

U.S. PATENT DOCUMENTS

(Continued)

FOREIGN PATENT DOCUMENTS

DE	10201134 A1	7/2003
DE	102012004117 A1	9/2013
WO	2017/033036 A1	3/2017

OTHER PUBLICATIONS

Intellectual Property Office (the United Kingdom), Search Report issued in corresponding Application No. GB1710445.6, dated Nov. 30, 2017.

Primary Examiner — Timothy K Trieu

Assistant Examiner — Dakota Marin

(74) Attorney, Agent, or Firm — Stites & Harbison,

PLLC; Jeffrey A. Haeberlin; Gary N. Stewart

(57) ABSTRACT

A sole (100) or inner sole for a shoe is provided. The sole (100) or inner sole comprises: a toe region (28) for supporting a user's toes; a forefoot region (26) for supporting a user's forefoot; a midfoot region (24) for supporting a user's arch; and a heel region (22) for supporting a user's heel. A longitudinal direction (X) extends from the heel region (22) towards the toe region (28). A lateral direction (Y) transverse to the longitudinal direction (X) extends from an inner side to an outer side of the sole (100) or inner sole. A plurality of force sensors (10) distributed throughout the sole (100) or inner sole. The plurality of force sensors (10) comprise: a first lateral row of force sensors (10) in the toe region (28); a second lateral row of force sensors (10) in the forefoot region (26); a first longitudinal row of force sensors (10) along the inner side of the sole (100) or inner sole from the heel region (22) to the midfoot region (24); and a second longitudinal row of force sensors (10) along the outer side of (Continued)

